



STABLE

STANDING

switches off the feed.

No overturning!

Once the front axle has exceeded the minimum

distance to the floor, the KDF1200-E automatically

EASY OPERATING

DUE TO ELECTRIC FEED AND SAW BLADE RAISE/ **LOWER MOTORS**

FEATURES NOF1200-E







VARIABLE **BLADE SPEED**

SOFT START AND VARIABLE ALLOWING THE BLADE TO WORK AT OPTIMUM SPEED

No complex belt change.

INTELLIGENT OPTIONAL SAW BLADE MOUNTING CONTROL

with cut supervision and attendance check.

Reliable and intuitive operation via joystick and comfortable quick selection through selector switch. Clear optical signals (e.g. permanent light, flash) support error detection.

Saw blades with different bore and location holes can be used due to interchangable flanges.

Ø 25.4 Ø 60 mm

Call our sales department for suitable saw blades from the series ONYX and LUXOR +49 5257 507-0

MANUAL **OPERATION**

All feed adjustments can be hand operated



COOLING WATER

WATER COUPLING WITH FLOW DISPLAY, **ADJUSTABLE VALVE** AND ON-OFF TAP

Fine adjustment by means of needle valve. No resetting of the water amount necessary.

DRIVES Company of the Compan

PLATFORM OUT, JUMP ON. AND DRIVE!

FOR SAFE LOADING/ UNLOADING

PRECISE ACCURATE AND STRAIGHT BY USING THE CUTTING GUIDE

HINGED BLADE GUARD

AND EASY SAW BLADE CHANGE



L/H+R/H CUTTING

Saw blade can be mounted on either side of

SPANNER FLATS

ON THE DRIVE SHAFT

For easy removal of the saw blade



TECHNICAL DETAILS NDF1200-E

MOTOR: electric 400 V / 50 Hz

ELECTRICAL CONNECTION: 32 A
CUTTING POWER: 15 kW

SPEED: continuously variable from 700 - 2,700 rpm

BLADE DIAMETER: max. Ø 1200 mm

BALDE SHAFT: Ø 25.40 mm | Ø 60 mm changeable

SAW BLADE MOUNTING: right or left
CUTTING DEPTH: max. 510 mm

DEPTH ADJUSTMENT: electrical / manual adjustable

FEED: electrical / manual adjustable

DIMENSIONS (L x W x H): 1300 x 800 x 1180 mm

WEIGHT: approx. 535 kg

ARTICLE NO.: 50-500

DEMONSTRATION?











